Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-881-0390

Section Quantity: 1 **Body Style:** Rectangular w/mounting holes/slots **Reliability Indicator:** Not established **Terminal Length:** Between 0.469 inches and 0.531 inches Mounting Hole Diameter: Between 0.088 inches and 0.098 inches Shaft Diameter: Between 0.120 inches and 0.130 inches Shaft Length: Between 0.040 inches and 0.060 inches **Body Length:** Between 1.234 inches and 1.266 inches **Body Width:** Between 0.283 inches and 0.297 inches **Body Height:** Between 0.328 inches and 0.359 inches Shaft Style: Round, slotted Shaft Bearing Type: Bearing Actuator Type: Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** Between 9360.0 and 10080.0 **Maximum Starting Torque:** 8.00 inch-ounces Maximum Running Torque: 8.00 inch-ounces **Center To Center Distance Between Terminals:** Between 0.695 inches and 0.705 inches **Fragility Factor:** Moderately rugged Lateral Distance Between Mounting Hole Centers: Between 0.995 inches and 1.005 inches **Mounting Facility Quantity:** 2

Terminal Location:

Lower adjacent side two rows

NSN 5905-00-881-0390

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Mounting Method:
Terminal and unthreaded hole
Center To Center Distance Between Terminal Rows:
Between 0.095 inches and 0.105 inches
Features Provided:
Humidity proof
Cubic Measure:
0.125 cubic inches
Electrical Resistance Per Section:
100.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
Between 9360.0 and 10080.0
Center To Center Distance Between Center Terminal And Outside Terminal:
Between 0.295 inches and 0.305 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
175.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-250.0/+0.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
85.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0