

View Online at <https://aerobasegroup.com/nsn/5905-00-881-3557>

**Section Quantity:**

2

**Body Style:**

Cylindrical servo mounted

**Reliability Indicator:**

Not established

**Pilot Diameter:**

0.9680 inches

**Pilot Length:**

0.0620 inches

**Undercut Diameter:**

0.968 inches

**Undercut Width:**

0.0620 inches

**Body Diameter:**

1.062 inches

**Shaft Diameter:**

0.125 inches

**Shaft Length:**

0.375 inches

**Body Length:**

1.375 inches

**Mounting Lip Diameter:**

0.9750 inches

**Mounting Lip Depth:**

0.0620 inches

**Shaft Style:**

Round

**Actuator Type:**

Single shaft

**Terminal Location:**

Radially positioned over more than half the circumference

**Mounting Method:**

Clamp ring

**Electrical Resistance Per Section:**

1.0 kilohms all sections

**Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:**

50.0 all sections

**Rotary Actuator Travel In Angular Deg:**

360.0

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

150.0 all sections

**Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:**

-100.0/+100.0 all sections

**Power Dissipation Rating Per Section In Watts:**

1.0 free air all sections

**Fixed Tap Quantity Per Section:**

1 all sections

**Tap Location Tolerance Per Section:**

-0.1/+0.1 degrees angular rotation all sections

**Resistance Tolerance Per Section In Percent:**

-20.0/+20.0 all sections

**Actuator Travel Control Feature:**

Stops

**Tap Location From Ccw Terminal Per Section In Ohms:**

5.0 all sections

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

85.0 all sections

**Standard Taper Curve Per Section:**

A all sections

**Terminal Type And Quantity:**

12 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A002a0