NSN 5905-00-882-2213

Section Quantity:

Cylindrical bushing mounted

Body Style:

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-882-2213

Body Diameter:
2.060 inches
Shaft Diameter:
Between 0.2494 inches and 0.2498 inches
Shaft Length:
0.880 inches
Mounting Bushing Length:
Between 0.296 inches and 0.391 inches
Body Length:
1.250 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Maximum Starting Torque:
5.00 inch-ounces
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
5.000 kilohms single section
Function Conformity Tolerance Per Section:
-1.00/+1.00 single section
Power Dissipation Rating Per Section In Watts:
0.5 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Function Characteristic Per Section:
Single section 360 degrees sine-cosine
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section

NSN 5905-00-882-2213

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Terminal Type And Quantity:
2 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiia:

A002a0