Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-882-4296

Section	Quantity:

1

Body Style:

Cylindrical

**Reliability Indicator:** 

Not established

**Overall Length:** 

0.535 inches

Terminal Length:

0.300 inches

Body Diameter:

0.500 inches

Body Length:

#### 0.235 inches

**Overall Diameter:** 

0.500 inches

Actuator Type:

Flush drive with slot-hole

# Effective Electrical Rotation In Deg Angular Rotation:

315.0

# Center To Center Distance Between Terminals:

0.200 inches

#### **Terminal Location:**

Rear end

#### **Mounting Method:**

Terminal

## **Electrical Resistance Per Section:**

100.0 ohms single section

## **Rotary Actuator Travel In Angular Deg:**

315.0

## Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

## Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

## **Power Dissipation Rating Per Section In Watts:**

1.0 free air single section

# **Resistance Tolerance Per Section In Percent:**

-5.0/+5.0 single section

# **Actuator Travel Control Feature:**

Stops

#### Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

55.0 single section

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Standard Taper Curve Per Section:

A single section

# Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0