

View Online at <https://aerobasegroup.com/nsn/5905-00-882-4360>

**Section Quantity:**

1

**Body Style:**

Cylindrical bushing mounted

**Reliability Indicator:**

Not established

**Body Diameter:**

0.720 inches

**Shaft Diameter:**

0.156 inches

**Shaft Length:**

0.250 inches

**Body Length:**

0.328 inches

**Shaft Style:**

Round

**Actuator Type:**

Double ended shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

245.0

**End Application:**

Tarawa class lha; nimitz class cvn; emory s. Land class as; sturgeon class ssn (637); virginia class cgn (41); oliver perry class ffg; ticonderoga class cg (47); spruance class dd (963); forrestal class cv

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Tab

**Electrical Resistance Per Section:**

1.0 megohms single section

**Rotary Actuator Travel In Angular Deg:**

300.0

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

85.0 single section

**Power Dissipation Rating Per Section In Watts:**

0.25 free air single section

**Resistance Tolerance Per Section In Percent:**

-30.0/+30.0 single section

**Actuator Travel Control Feature:**

Stops

**Criticality Code Justification:**

Feat

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

55.0 single section

**Standard Taper Curve Per Section:**

A single section

**Special Features:**

Weapon system essential

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0