## NSN 5905-00-883-0424

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-883-0424

View C	Online at https://aerobasegroup.com/nsn/5905-00-883-
Section	on Quantity:
1	
Body	Style:
Rectar	ngular w/mounting holes/slots
Reliab	ility Indicator:
Not es	tablished
Overa	II Length:
1.312	inches
Termi	nal Length:
Betwe	en 0.484 inches and 0.516 inches
Overa	II Height:
0.812	inches
Overa	II Width:
Betwe	en 0.270 inches and 0.290 inches
Mount	ing Hole Diameter:
0.086	inches
Shaft	Diameter:
Betwe	en 0.109 inches and 0.141 inches
Shaft	Length:
Betwe	en 0.046 inches and 0.078 inches
Body	Length:
Betwe	en 1.234 inches and 1.266 inches
Body	Width:
Betwe	en 0.234 inches and 0.266 inches
Body	Height:
Betwe	en 0.296 inches and 0.328 inches
Shaft	Style:
Round	, slotted
Actua	tor Type:
Single	shaft
Effect	ive Electrical Rotation In Deg Angular Rotation:
9000.0	
Cente	r To Center Distance Between Terminals:
Betwe	en 0.690 inches and 0.710 inches
Latera	l Distance Between Mounting Hole Centers:
Betwe	en 0.995 inches and 1.005 inches
Mount	ing Facility Quantity:
2	
Termi	nal Location:
Lower	adjacent side single row
Mount	ing Method:

**Mounting Method:** 

Terminal and unthreaded hole

## NSN 5905-00-883-0424

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Center To Center Distance Between Terminal Rows:
0.100 inches
Electrical Resistance Per Section:
3.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
0.000
Center To Center Distance Between Center Terminal And Outside Terminal:
Between 0.290 inches and 0.310 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
05.0 single section
Power Dissipation Rating Per Section In Watts:
0.5 free air single section
Resistance Tolerance Per Section In Percent:
10.0/+10.0 single section
Actuator Travel Control Feature:
Clutch
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
20.0/+20.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
25.0 single section
Standard Taper Curve Per Section:
A single section
Ferminal Type And Quantity:
3 pin
Shelf Life:
N/a
Jnit Of Measure:
-
Demilitarization:
No
Filg:
A002a0