NSN 5905-00-883-0927

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-883-0927 **Section Quantity: Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 1.485 inches **Terminal Length:** 0.360 inches **Body Diameter:** 1.280 centimeters **Shaft Diameter:** Between 0.248 inches and 0.251 inches **Shaft Length:** Between 0.844 inches and 0.906 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 1.250 inches **Overall Diameter:** 1.640 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius:** Between 0.516 inches and 0.546 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Lower adjacent side single row **Mounting Method:** Standard bushing

Electrical Resistance Per Section:

7.5 percent, rated amperes c and better flooring

NSN 5905-00-883-0927

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watts: 2.0 7th secondary quality Resistance Tolerance Per Section In Percent: -10.0/+10.0 single section Standard Taper Curve Per Section: A single section Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure: - Demilitarization: No

Fiig: A002a0