## NSN 5905-00-883-0977

No

Inductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-883-0977

| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:   |
|---|
| -260.0/+260.0   |
| Electrical Resistance:  |
| 47.000 ohms   |
| Resistance Tolerance In Percent:  |
| -5.000/+5.000   |
| Ambient Tempurature In Deg Celsius At Full Rated Power:   |
| 25.0  |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:   |
| 350.0   |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius:  |
| -55.0/+350.0  |
| Inclosure Method:   |
| Encapsulated  |
| Terminal Type:  |
| Tab, solder lug   |
| Reliability Indicator:  |
| Not established   |
| Terminal Length:  |
| 0.407 inches  |
| Body Length:  |
| 6.000 inches  |
| Body Width:   |
| 1.187 inches  |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:  |
| 6.750 inches  |
| Power Dissipation Rating In Watts:  |
| 91.000 free air   |
| Terminal Width:   |
| 0.265 inches  |
| Mounting Hole Size:   |
| 0.196 inches  |
| Style Designator:   |
| Terminals one edge  |
| Test Data Document:   |
| 81349-milr26-2 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; |
| excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental         |
| and performance requirements and test conditions that are shown as "typical", "average", "", etc.).   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
| <del></del>   |
| Demilitarization:   |

## NSN 5905-00-883-0977

Inductive Wire Wound Fixed Resistor - Page 2 of 2



Fiig:

A001a0