NSN 5905-00-883-3140

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 1



| Tromproductor received transport received |
|---|
| View Online at https://aerobasegroup.com/nsn/5905-00-883-3140 |
| Section Quantity: |
| 1 |
| Reliability Indicator: |
| Not established |
| Shaft Diameter: |
| 0.250 inches |
| Shaft Length: |
| 0.624 inches |
| Shaft Style: |
| Round, slotted |
| Actuator Type: |
| Single shaft |
| Nonturn Device Location: |
| At 9 oclock |
| Nonturn Device Radius: |
| 0.531 inches |
| Screw Thread Diameter: |
| 0.375 inches |
| Screw Thread Series Designator: |
| Unef |
| Screw Thready Qty Per Inch (tpi): |
| 32.0 |
| Mounting Method: |
| Locking bushing |
| Electrical Resistance Per Section: |
| 100.0 kilohms single section |
| Power Dissipation Rating Per Section In Watts: |
| 2.0 free air single section |
| Resistance Tolerance Per Section In Percent: |
| -10.0/+10.0 single section |
| Standard Taper Curve Per Section: |
| A single section |
| Terminal Type And Quantity: |
| 3 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig:

A002a0