## NSN 5905-00-883-3735

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



Tronpredictor ville violatia variable recoloter i age i of 2	
View Online at https://aerobasegroup.com/nsn/5905-00-883-3735	
Section Quantity:	
1	
Body Style:	
Cylindrical bushing mounted	
Reliability Indicator:	
Not established	
Overall Length:	
Between 1.944 inches and 2.186 inches	
Body Diameter:	
Between 1.100 inches and 1.310 inches	
Shaft Diameter:	
Between 0.248 inches and 0.251 inches	
Shaft Length:	
Between 0.844 inches and 0.906 inches	
Mounting Bushing Length:	
Between 0.360 inches and 0.390 inches	
Body Length:	
Between 0.850 inches and 0.970 inches	
Overall Diameter:	
1.750 inches	
Shaft Style:	
Round, slotted	
Switch Type:	
Rotary	
Switch Voltage Rating In Volts:	
117.0	
Actuator Type:	
Single shaft	
Effective Electrical Rotation In Deg Angular Rotation:	
Between 220.0 and 285.0	
Maximum Starting Torque:	
6.00 inch-ounces	
Maximum Stop Torque:	
128.00 inch-ounces	
Nonturn Device Location:	

**Nonturn Device Location:** 

At 9 oclock

**Nonturn Device Radius:** 

Between 0.516 inches and 0.546 inches

**Switch Operating Position:** 

Start of rotation

**Switch Contact Arrangement:** 

Single pole, single throw, normally open, both positions maintained

## NSN 5905-00-883-3735

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Features Provided:
Switch
Electrical Resistance Per Section:
6.0 ohms single section
Rotary Actuator Travel In Angular Deg:
Between 290.0 and 305.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
105.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Switch Current Type And Rating In Amps:
3.000 ac
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
5 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A002a0