## NSN 5905-00-883-4840

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-883-4840

Electrical Resistance: 154.000 ohms Resistance Tolerance In Percent: 1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+105.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter:
Resistance Tolerance In Percent: 1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+105.0 nclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established
Resistance Tolerance In Percent: 4.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Fempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+105.0 Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established
Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+105.0 nclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established
Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Fempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+105.0 Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  150.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  150.0/+105.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Not established
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  150.0  Fempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0/+105.0  nclosure Method:  Encapsulated  Ferminal Type:  Wire lead  Reliability Indicator:  Not established
Tempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0/+105.0  nclosure Method: Encapsulated  Terminal Type: Wire lead  Reliability Indicator: Not established
Tempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0/+105.0  nclosure Method: Encapsulated  Terminal Type: Wire lead  Reliability Indicator: Not established
55.0/+105.0  nclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established
nclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established
Encapsulated  Ferminal Type:  Wire lead  Reliability Indicator:  Not established
Ferminal Type:  Wire lead  Reliability Indicator:  Not established
Wire lead  Reliability Indicator:  Not established
Reliability Indicator: Not established
Not established
3ody Diameter:
0.125 inches
Body Length:
0.375 inches
Power Dissipation Rating In Watts:
0.125 free air
Style Designator:
Axial terminal each end
Test Data Document:
31349-mil-r-10509 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
31349-mil-r-10509/1 government specification
Shelf Life:
N/a
Jnit Of Measure:
-
Demilitarization:
No
Filg:
A001a0