

View Online at <https://aerobasegroup.com/nsn/5905-00-884-1037>

**Section Quantity:**

2

**Body Style:**

Cylindrical bushing mounted

**Body Diameter:**

0.937 inches

**Shaft Diameter:**

Between 0.187 inches and 0.265 inches

**Shaft Length:**

Between 0.187 inches and 0.500 inches

**Mounting Bushing Length:**

0.375 inches

**Body Length:**

0.875 inches

**Shaft Style:**

Round, slotted

**Actuator Type:**

Double ended shaft

**Maximum Starting Torque:**

6.00 inch-ounces

**Nonturn Device Location:**

At 9 oclock

**Nonturn Device Radius:**

0.531 inches

**Screw Thread Diameter:**

0.375 inches

**Screw Thread Series Designator:**

Unef

**Screw Thready Qty Per Inch (tpi):**

32.0

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Standard bushing

**Electrical Resistance Per Section:**

100.000 ohms c and better finish

**Power Dissipation Rating Per Section In Watts:**

1.0 7th secondary finish

**Resistance Tolerance Per Section In Percent:**

-20.0/+20.0 single section

**Standard Taper Curve Per Section:**

A single section

**Terminal Type And Quantity:**

6 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0