Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-884-1456

Section Quantity:

1

Body Style:

Rectangular w/mounting holes/slots

Reliability Indicator:

Not established

Overall Length:

1.312 inches

Overall Height:

0.953 inches

Overall Width:

0.953 inches

Shaft Diameter:

Between 0.109 inches and 0.141 inches

Shaft Length:

Between 0.046 inches and 0.078 inches

Body Length:

Between 1.234 inches and 1.266 inches

Body Width:

Between 0.234 inches and 0.266 inches

Body Height:

Between 0.343 inches and 0.375 inches

Shaft Style:

Round, cross slotted

Actuator Type:

Single shaft

Center To Center Distance Between Terminals:

0.700 inches

Terminal Location:

Lower adjacent side single row

Mounting Method:

Terminal

Center To Center Distance Between Terminal Rows:

0.100 inches

Features Provided:

Nonmetallic shaft

Electrical Resistance Per Section:

200.000 ohms single section

Center To Center Distance Between Center Terminal And Outside Terminal:

Between 0.290 inches and 0.310 inches

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

100.0 single section

NSN 5905-00-884-1456

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watts:

0.333 free air single section

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

50.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 connector, receptacle

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0