## NSN 5905-00-884-1498

**Section Quantity:** 

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-884-1498

1
Body Style:
Rectangular w/mounting holes
Reliability Indicator:
Not established
Overall Length:
0.530 inches
Overall Height:
0.500 inches
Overall Width:
0.190 inches
Mounting Hole Diameter:
0.093 inches
Shaft Diameter:
0.093 inches
Shaft Length:
0.030 inches
Body Length:
0.500 inches
Body Width:
0.190 inches
Body Height:
0.500 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
8280.0
Lateral Distance Between Mounting Hole Centers:
0.520 inches
Mounting Facility Quantity:
2
Terminal Location:
Rear end
Mounting Method:
Unthreaded hole
Electrical Resistance Per Section:
1.0 percent, rated amperes c and better flooring
Rotary Actuator Travel In Angular Deg:
8280.0

## NSN 5905-00-884-1498

No Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



## Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 150.0 single section **Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:** -50.0/+50.0 single section **Power Dissipation Rating Per Section In Watts:** 1.5 7th secondary quality **Resistance Tolerance Per Section In Percent:** -5.0/+5.0 single section **Actuator Travel Control Feature:** Clutch Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 wire lead Shelf Life: N/a **Unit Of Measure: Demilitarization:**