NSN 5905-00-885-1705

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-885-1705 **Section Quantity: Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 1.690 inches **Body Diameter:** 1.300 inches **Shaft Diameter:** 0.2497 inches **Shaft Length:** 0.880 inches **Mounting Bushing Length:** 0.320 inches **Body Length:** 0.630 inches **Overall Diameter:** 1.300 inches **Shaft Style:** Round **Shaft Bearing Type:** Sleeve **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 352.0 **Maximum Starting Torque:** 2.00 inch-ounces **Maximum Running Torque:** 2.00 inch-ounces **Nonturn Device Location:** At 6 oclock **Nonturn Device Radius:** 0.562 inches **Shaft End Play:** 0.007 inches **Shaft Runout:**

0.0025 inches **Lateral Runout:** 0.005 inches

NSN 5905-00-885-1705

Precision Wire Wound Variable Resistor - Page 2 of 3



Pilot Diameter Runout:
0.0025 inches
Shaft Radial Play:
0.004 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Rear end
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
1.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-0.50/+0.50 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
105.0 single section
Power Dissipation Rating Per Section In Watts:
2.75 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-2.0/+2.0 single section
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Test Data Document:
73760-108081 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
3 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

NSN 5905-00-885-1705

Precision Wire Wound Variable Resistor - Page 3 of 3



Fiig:

A002a0