

View Online at <https://aerobasegroup.com/nsn/5905-00-887-5448>

**Section Quantity:**

1

**Body Style:**

Cylindrical

**Reliability Indicator:**

Not established

**Overall Length:**

1.112 inches

**Terminal Length:**

0.550 inches

**Body Diameter:**

0.500 inches

**Body Length:**

0.531 inches

**Overall Diameter:**

0.500 inches

**Actuator Type:**

Flush drive with slot-hole

**Effective Electrical Rotation In Deg Angular Rotation:**

295.0

**Center To Center Distance Between Terminals:**

0.200 inches

**Fragility Factor:**

Moderately delicate

**Terminal Location:**

Rear end

**Mounting Method:**

Terminal

**Features Provided:**

Humidity proof

**Electrical Resistance Per Section:**

250.0 ohms c and better flooring

**Rotary Actuator Travel In Angular Deg:**

295.0

**Center To Center Distance Between Center Terminal And Outside Terminal:**

0.100 inches

**Resistance Temperature Characteristic Range Per Section In Percent:**

+0.0/+4.5 -55 degrees celsius single section and +0.0/+2.5 -25 degrees celsius single section and +0.0/+1.5 0 degrees celsius single section and -1.5/+1.5 85 degrees celsius single section and +0.0/+3.5 120 degrees celsius single section

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

120.0 single section

**Power Dissipation Rating Per Section In Watts:**

0.25 2nd winding quality

**Resistance Tolerance Per Section In Percent:**

-20.0/+20.0 single section

**Actuator Travel Control Feature:**

Stops

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

70.0 single section

**Standard Taper Curve Per Section:**

A single section

**Terminal Type And Quantity:**

3 pin

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A002a0