Nonprecision Wire Wound Variable Resistor - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5905-00-887-5965

Section Quantity:

1

Body Style:

Rectangular w/mounting holes

Reliability Indicator:

Not established

Overall Length:

1.000 inches

Terminal Length:

0.500 inches

Overall Height:

Between 0.490 inches and 0.510 inches

Overall Width:

Between 0.210 inches and 0.230 inches

Mounting Hole Diameter:

Between 0.075 inches and 0.081 inches

Shaft Diameter:

Between 0.078 inches and 0.088 inches

Shaft Length:

Between 0.025 inches and 0.045 inches

Body Length:

Between 0.490 inches and 0.510 inches

Body Width:

Between 0.210 inches and 0.230 inches

Body Height:

Between 0.490 inches and 0.510 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

9000.0

Maximum Starting Torque:

5.00 inch-ounces

Center To Center Distance Between Terminals:

0.200 inches

Lateral Distance Between Mounting Hole Centers:

Between 0.515 inches and 0.530 inches

Mounting Facility Quantity:

2

Terminal Location:

Left adjacent side single row

NSN 5905-00-887-5965

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



| Mounting Method:Unthreaded holeElectrical Resistance Per Section:100.0 ohms single sectionRotary Actuator Travel In Angular Deg:9000.0Center To Center Distance Between Center Terminal And Outside Terminal:Between 0.090 inches and 0.110 inchesAmbient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:175.0 single sectionPower Dissipation Rating Per Section In Watts:1.0 free air single sectionResistance Tolerance Per Section In Percent:-5.0/+5.0 single section |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Electrical Resistance Per Section: 100.0 ohms single section Rotary Actuator Travel In Angular Deg: 9000.0 Center To Center Distance Between Center Terminal And Outside Terminal: Between 0.090 inches and 0.110 inches Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 175.0 single section Power Dissipation Rating Per Section In Watts: 1.0 free air single section Resistance Tolerance Per Section In Percent: -5.0/+5.0 single section |
| 100.0 ohms single section Rotary Actuator Travel In Angular Deg: 9000.0 Center To Center Distance Between Center Terminal And Outside Terminal: Between 0.090 inches and 0.110 inches Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 175.0 single section Power Dissipation Rating Per Section In Watts: 1.0 free air single section Resistance Tolerance Per Section In Percent: -5.0/+5.0 single section |
| Rotary Actuator Travel In Angular Deg:9000.0Center To Center Distance Between Center Terminal And Outside Terminal:Between 0.090 inches and 0.110 inchesAmbient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:175.0 single sectionPower Dissipation Rating Per Section In Watts:1.0 free air single sectionResistance Tolerance Per Section In Percent:-5.0/+5.0 single section |
| 9000.0 Center To Center Distance Between Center Terminal And Outside Terminal: Between 0.090 inches and 0.110 inches Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 175.0 single section Power Dissipation Rating Per Section In Watts: 1.0 free air single section Resistance Tolerance Per Section In Percent: -5.0/+5.0 single section |
| Center To Center Distance Between Center Terminal And Outside Terminal: Between 0.090 inches and 0.110 inches Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 175.0 single section Power Dissipation Rating Per Section In Watts: 1.0 free air single section Resistance Tolerance Per Section In Percent: -5.0/+5.0 single section |
| Between 0.090 inches and 0.110 inches Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 175.0 single section Power Dissipation Rating Per Section In Watts: 1.0 free air single section Resistance Tolerance Per Section In Percent: -5.0/+5.0 single section |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 175.0 single section Power Dissipation Rating Per Section In Watts: 1.0 free air single section Resistance Tolerance Per Section In Percent: -5.0/+5.0 single section |
| 175.0 single section Power Dissipation Rating Per Section In Watts: 1.0 free air single section Resistance Tolerance Per Section In Percent: -5.0/+5.0 single section |
| Power Dissipation Rating Per Section In Watts: 1.0 free air single section Resistance Tolerance Per Section In Percent: -5.0/+5.0 single section |
| 1.0 free air single section Resistance Tolerance Per Section In Percent: -5.0/+5.0 single section |
| Resistance Tolerance Per Section In Percent: -5.0/+5.0 single section |
| -5.0/+5.0 single section |
| - |
| |
| Actuator Travel Control Feature: |
| Clutch |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: |
| 70.0 single section |
| Standard Taper Curve Per Section: |
| A single section |
| Terminal Type And Quantity: |
| 3 pin |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A002a0 |
| |