NSN 5905-00-887-9470

Nonprecision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-887-9470

View Online at https://aerobasegroup.com/nsn/5905-00-887-9
Section Quantity:
3
Body Style:
Cylindrical servo mounted
Reliability Indicator:
Not established
Pilot Diameter:
Between 1.0295 inches and 1.0300 inches
Pilot Length:
Between 0.0300 inches and 0.0500 inches
Undercut Diameter:
Between 1.0295 inches and 1.030 inches
Undercut Width:
Between 0.0500 inches and 0.0700 inches
Body Diameter:
Between 1.080 inches and 1.100 inches
Shaft Diameter:
0.125 inches
Shaft Length:
Between 0.743 inches and 0.812 inches
Body Length:
1.260 inches
Mounting Lip Diameter:
Between 1.0800 inches and 1.1000 inches
Mounting Lip Depth:
Between 0.0500 inches and 0.0700 inches
Undercut Diameter:
Between 0.116 inches and 0.119 inches
Shaft Style:
Round, stepped
Shaft Bearing Type:
Ball
Actuator Type:
Double ended shaft
Effective Electrical Rotation In Deg Angular Rotation:
343.0
Maximum Starting Torque:
0.60 inch-ounces
Maximum Running Torque:
0.50 inch-ounces

Shaft End Play: 0.001 inches

NSN 5905-00-887-9470

Nonprecision Wire Wound Variable Resistor - Page 2 of 3



Shaft Runout:
0.006 inches
Lateral Runout:
0.001 inches
Pilot Diameter Runout:
0.001 inches
Shaft Radial Play:
0.001 inches
Mechanical Backlash In Deg Angular Rotation:
0.5
Undercut Length:
Between 0.012 inches and 0.014 inches
Terminal Location:
Radially positioned over more than half the circumference
Mounting Method:
Clamp ring
Features Provided:
Nonmetallic shaft
Electrical Resistance Per Section:
20.0 kilohms all sections
Rotary Actuator Travel In Angular Deg:
360.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 all sections
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-400.0/+400.0 all sections
Power Dissipation Rating Per Section In Watts:
1.0 free air all sections
Fixed Tap Quantity Per Section:
1 all sections
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 all sections
Actuator Travel Control Feature:
Continuous motion
Tap Location From Ccw Terminal Per Section In Ohms:
100.0 all sections
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 all sections
Terminal Type And Quantity:
12 turret
Shelf Life:
N/a
Unit Of Measure:

-

NSN 5905-00-887-9470

Nonprecision Wire Wound Variable Resistor - Page 3 of 3



em			

No

Fiig:

A002a0