

View Online at <https://aerobasegroup.com/nsn/5905-00-888-5579>

Section Quantity:

3

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Body Diameter:

1.562 mils and 1.687 centimeters

Shaft Length:

0.562 inches

Mounting Bushing Length:

0.250 inches

Body Length:

Between 4.156 inches and 4.218 inches

Shaft Style:

Round

Shaft Bearing Type:

Sleeve

Actuator Type:

Single shaft

Nonturn Device Location:

At 12 oclock

Nonturn Device Radius:

0.500 inches

Fragility Factor:

Moderately rugged

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Features Provided:

Humidity proof

Electrical Resistance Per Section:

50.0 ohms c and better

Power Dissipation Rating Per Section In Watts:

25.0 7th secondary at 10'30 oclock

Resistance Tolerance Per Section In Percent:

-10.0/+20.0 all sections

Standard Taper Curve Per Section:

A all sections

Terminal Type And Quantity:

9 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0