

View Online at <https://aerobasegroup.com/nsn/5905-00-889-2166>

**Section Quantity:**

1

**Body Style:**

Rectangular w/mounting holes

**Reliability Indicator:**

Not established

**Terminal Length:**

6.000 inches

**Shaft Diameter:**

0.093 inches

**Shaft Length:**

0.085 inches

**Mounting Stud Length:**

0.218 inches

**Body Length:**

0.403 inches

**Body Width:**

0.218 inches

**Body Height:**

0.375 inches

**Shaft Style:**

Round, slotted

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

9000.0

**Maximum Starting Torque:**

5.00 inch-ounces

**Lateral Distance Between Mounting Hole Centers:**

0.419 inches

**Screw Thread Diameter:**

0.073 inches

**Screw Thread Series Designator:**

Unf

**Screw Thread Qty Per Inch (tpi):**

72.0

**Mounting Facility Quantity:**

2

**Terminal Location:**

Lower adjacent side single row

**Mounting Method:**

Threaded stud

**Electrical Resistance Per Section:**

20.0 kilohms single section

**Rotary Actuator Travel In Angular Deg:**

9000.0

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

150.0 single section

**Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:**

-70.0/+70.0 single section

**Power Dissipation Rating Per Section In Watts:**

1.0 free air single section

**Resistance Tolerance Per Section In Percent:**

-5.0/+5.0 single section

**Actuator Travel Control Feature:**

Continuous motion

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

70.0 single section

**Standard Taper Curve Per Section:**

A single section

**Test Data Document:**

13499-377-0718-350 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

3 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0