Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-889-2166

Section Quantity:

1

- Body Style: Rectangular w/mounting holes
- Reliability Indicator:
- Not established
- **Terminal Length:**
- 6.000 inches
- Shaft Diameter:
- 0.093 inches
- Shaft Length:
- 0.085 inches
- Mounting Stud Length:
- 0.218 inches
- Body Length:

0.403 inches

- **Body Width:**
- 0.218 inches
- Body Height:
- 0.375 inches
- Shaft Style:
- Round, slotted
- Actuator Type:
- Single shaft
- Effective Electrical Rotation In Deg Angular Rotation:
- 9000.0
- Maximum Starting Torque:
- 5.00 inch-ounces
- Lateral Distance Between Mounting Hole Centers:
- 0.419 inches
- Screw Thread Diameter:
- 0.073 inches
- Screw Thread Series Designator:
- Unf
- Screw Thready Qty Per Inch (tpi):
- 72.0
- **Mounting Facility Quantity:**
- 2
- Terminal Location:
- Lower adjacent side single row
- Mounting Method:
- Threaded stud

NSN 5905-00-889-2166

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:
20.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
9000.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-70.0/+70.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Continuous motion
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Test Data Document:
13499-377-0718-350 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
3 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0