## NSN 5905-00-889-2553

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-889-2553 **Section Quantity: Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Terminal Length:** Between 0.147 inches and 0.157 inches **Body Diameter:** Between 0.495 inches and 0.505 inches **Shaft Diameter:** Between 0.120 inches and 0.130 inches Shaft Length: Between 0.382 inches and 0.387 inches **Mounting Bushing Length:** Between 0.296 inches and 0.328 inches **Body Length:** 0.305 inches **Shaft Style:** Round, slotted **Shaft Bearing Type:** Bearing **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 240.0 **Maximum Starting Torque:** 0.20 inch-ounces **Maximum Running Torque:** 0.20 inch-ounces **Screw Thread Diameter:** 0.250 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Rear end **Mounting Method:** Standard bushing

10.0 kilohms single section

**Electrical Resistance Per Section:** 

## NSN 5905-00-889-2553

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Rotary Actuator Travel In Angular Deg:
300.0
Function Conformity Tolerance Per Section:
1.00/+1.00 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
50.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Fixed Tap Quantity Per Section:
single section
Resistance Tolerance Per Section In Percent:
5.0/+5.0 single section
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Test Data Document:
39015-84136-2 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Ferminal Type And Quantity:
solder stud
Shelf Life:
N/a
Jnit Of Measure:
-
Demilitarization:
No.
Filg:
A002a0