## NSN 5905-00-889-5460

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-889-5460 **Section Quantity:** 1 **Body Style:** Rectangular w/mounting holes/slots **Reliability Indicator:** Not established **Overall Height:** 0.360 inches **Overall Width:** 0.300 inches **Mounting Hole Diameter:** 0.086 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.030 inches **Body Length:** 1.340 inches **Body Width:** 0.300 inches **Body Height:** 0.360 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 9000.0 **Lateral Distance Between Mounting Hole Centers:** 1.000 inches **Mounting Facility Quantity: Terminal Location:** Rear end **Mounting Method:** Unthreaded hole

**Features Provided:** Humidity proof **Electrical Resistance Per Section:** 5.0 kilohms single section **Rotary Actuator Travel In Angular Deg:** 9000.0

## NSN 5905-00-889-5460

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



## Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 135.0 single section **Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:** -50.0/+50.0 single section **Power Dissipation Rating Per Section In Watts:** 0.8 free air single section **Fixed Tap Quantity Per Section:** 1 single section **Tap Location Tolerance Per Section:** -50.0/+50.0 ohms single section **Resistance Tolerance Per Section In Percent:** -10.0/+10.0 single section **Actuator Travel Control Feature:** Clutch **Tap Location From Ccw Terminal Per Section In Ohms:** 2500.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 wire lead **Shelf Life:** N/a **Unit Of Measure: Demilitarization:** No