NSN 5905-00-890-4370

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-890-4370

Santian Overstitus
Section Quantity:
1
Body Style:
Rectangular
Reliability Indicator:
Not established Towning Lieuwith
Terminal Length: Between 0.172 inches and 0.192 inches
Shaft Diameter:
0.093 inches
Shaft Length:
0.080 inches
Body Length:
0.375 inches
Body Width: 0.190 inches
Body Height: 0.405 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft Effective Electrical Potation In Dog Angular Potation:
Effective Electrical Rotation In Deg Angular Rotation: Between 6480.0 and 10080.0
Maximum Starting Torque: 5.00 inch-ounces
Maximum Running Torque:
5.00 inch-ounces
Center To Center Distance Between Terminals:
0.200 inches
Fragility Factor: Moderately rugged
Terminal Location:
Lower adjacent side single row
Mounting Method:
Terminal
Electrical Resistance Per Section:
5.0 percent, rated amperes c and better flooring
Rotary Actuator Travel In Angular Deg: Between 6480.0 and 10080.0
Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

NSN 5905-00-890-4370

No Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 150.0 single section **Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:** -50.0/+50.0 single section **Power Dissipation Rating Per Section In Watts:** 1.0 7th secondary quality **Resistance Tolerance Per Section In Percent:** -5.0/+5.0 single section **Actuator Travel Control Feature:** Continuous motion Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 85.0 single section **Standard Taper Curve Per Section:** A single section **Special Features:** Sealed to permit cleaning in common solvents **Terminal Type And Quantity:** 3 pin Shelf Life: N/a **Unit Of Measure:** Demilitarization: