

View Online at <https://aerobasegroup.com/nsn/5905-00-890-4389>

**Section Quantity:**

1

**Body Style:**

Cylindrical

**Reliability Indicator:**

Not established

**Body Diameter:**

Between 0.780 inches and 0.790 inches

**Body Length:**

Between 0.417 inches and 0.427 inches

**Shaft Bearing Type:**

Bearing

**Actuator Type:**

Flush drive with slot-hole

**Effective Electrical Rotation In Deg Angular Rotation:**

240.0

**Maximum Starting Torque:**

10.00 inch-ounces

**Maximum Running Torque:**

10.00 inch-ounces

**Fragility Factor:**

Moderately rugged

**Terminal Location:**

Upper adjacent side two rows

**Mounting Method:**

Terminal

**Features Provided:**

Grounded contact arm

**Cubic Measure:**

0.433 cubic inches

**Electrical Resistance Per Section:**

150.0 ohms single section

**Rotary Actuator Travel In Angular Deg:**

Between 241.0 and 251.0

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

105.0 single section

**Power Dissipation Rating Per Section In Watts:**

1.5 free air single section

**Resistance Tolerance Per Section In Percent:**

-20.0/+20.0 single section

**Actuator Travel Control Feature:**

Clutch

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

55.0 single section

**Standard Taper Curve Per Section:**

A single section

**Terminal Type And Quantity:**

2 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0