NSN 5905-00-890-8527

Nonprecision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-890-8527 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 0.62500 inches Pilot Length: 0.06200 inches **Overall Length:** 2.205 inches **Undercut Diameter:** 0.781 inches **Undercut Width:** 0.06200 inches **Body Diameter:** 0.875 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.625 inches **Body Length:** 1.580 inches **Overall Diameter:** 1.250 inches **Mounting Lip Diameter:** 0.87500 inches **Mounting Lip Depth:** 0.06200 inches **Shaft Style:** Round **Shaft Bearing Type:** Ball **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 3406.0 **Maximum Starting Torque:**

0.70 inch-ouncesMaximum Running Torque:0.60 inch-ounces

NSN 5905-00-890-8527

Nonprecision Wire Wound Variable Resistor - Page 2 of 3



Maximum Stop Torque:
96.00 inch-ounces
Shaft End Play:
0.00500 inches
Shaft Radial Play:
0.002 inches
Terminal Location:
Radially positioned over more than half the circumference
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
2.000 kilohms single section
Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:
14.0 single section and 1080.0 single section
Rotary Actuator Travel In Angular Deg:
3600.0
Function Conformity Tolerance Per Section:
-0.10/+0.10 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
85.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Fixed Tap Quantity Per Section:
2 single section
Resistance Tolerance Per Section In Percent:
-3.0/+3.0 single section
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Terminal Type And Quantity:
5 solder stud
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

NSN 5905-00-890-8527

Nonprecision Wire Wound Variable Resistor - Page 3 of 3



Fiig:

A002a0