

View Online at <https://aerobasegroup.com/nsn/5905-00-890-9395>

**Section Quantity:**

2

**Body Style:**

Cylindrical bushing mounted

**Reliability Indicator:**

Not established

**Overall Length:**

2.157 inches

**Body Diameter:**

1.562 inches

**Shaft Diameter:**

0.250 inches

**Shaft Length:**

1.250 inches

**Mounting Bushing Length:**

0.375 inches

**Body Length:**

0.907 inches

**Body Inside Diameter:**

0.190 inches

**Overall Diameter:**

0.953 inches

**Undercut Diameter:**

0.188 inches

**Shaft Style:**

Round, stepped

**Shaft Bearing Type:**

Bearing

**Actuator Type:**

Dual concentric

**Nonturn Device Location:**

At 9 oclock

**Nonturn Device Radius:**

0.454 inches

**Undercut Length:**

0.625 inches

**Screw Thread Diameter:**

0.375 inches

**Screw Thread Series Designator:**

Unef

**Screw Thready Qty Per Inch (tpi):**

32.0

**Terminal Location:**

Upper adjacent side two rows

**Mounting Method:**

Locking bushing

**Electrical Resistance Per Section:**

5.0 kilohms all sections

**Power Dissipation Rating Per Section In Watts:**

0.5 free air all sections

**Resistance Tolerance Per Section In Percent:**

-20.0/+20.0 all sections

**Standard Taper Curve Per Section:**

A single section

**Terminal Type And Quantity:**

6 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0