NSN 5905-00-891-1682

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-891-1682 **Section Quantity: Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 1.9063 inches **Body Diameter:** 1.7813 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.906 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 2.5938 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 300.0 **Nonturn Device Location:** At 1 0clock and at 11: 00 oclock **Nonturn Device Radius:** 0.890 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Standard bushing

Electrical Resistance Per Section:

2.5 percent, rated amperes c and better v.G. Stepping

Rotary Actuator Travel In Angular Deg:

300.0

NSN 5905-00-891-1682

Precision Wire Wound Variable Resistor - Page 2 of 2



Function Conformity Tolerance Per Section: -0.25/+0.25 all sections **Power Dissipation Rating Per Section In Watts:** Any acceptable **Function Conformity Per Section:** All sections absolute conformity **Resistance Tolerance Per Section In Percent:** -1.0/+1.0 all sections **Actuator Travel Control Feature:** Stops **Function Characteristic Per Section:** All sections 360 degrees sine-cosine **Terminal Type And Quantity:** 24 tab, solder lug Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No Fiig: A002a0