

View Online at https://aerobasegroup.com/nsn/5905-00-892-0115

### Section Quantity:

1

## **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** Between 1.797 inches and 1.829 inches Shaft Diameter:

Between 0.2494 inches and 0.2497 inches

#### Shaft Length:

Between 0.421 inches and 0.453 inches

#### **Mounting Bushing Length:**

Between 0.297 inches and 0.329 inches

#### **Body Length:**

Between 1.984 inches and 2.016 inches

Shaft Style:

Round

#### Shaft Bearing Type:

Sleeve

#### Actuator Type:

Single shaft

#### Effective Electrical Rotation In Deg Angular Rotation:

3600.0

#### **Maximum Starting Torque:**

2.00 inch-ounces

#### Maximum Running Torque:

1.50 inch-ounces

#### **Nonturn Device Location:**

At 6 oclock

#### **Nonturn Device Radius:**

Between 0.547 inches and 0.579 inches

#### Shaft End Play:

0.005 inches

#### Shaft Runout:

0.0005 inches

#### Lateral Runout:

0.003 inches

#### **Pilot Diameter Runout:**

0.002 inches

#### Shaft Radial Play:

0.003 inches



## **Fragility Factor:** Moderately rugged **Screw Thread Diameter:** Between 0.359 inches and 0.391 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Longitudinally positioned on the circumference **Mounting Method:** Standard bushing **Features Provided:** Humidity proof **Cubic Measure:** 5.294 cubic inches **Electrical Resistance Per Section:** 2.0 kilohms single section **Rotary Actuator Travel In Angular Deg:** Between 3600.0 and 3604.0 **Function Conformity Tolerance Per Section:** -0.25/+0.25 single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 85.0 single section **Power Dissipation Rating Per Section In Watts:** 5.0 free air single section **Function Conformity Per Section:** Single section independent linearity **Resistance Tolerance Per Section In Percent:** -3.0/+3.0 single section **Actuator Travel Control Feature:** Continuous motion **Function Characteristic Per Section:** Single section linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section **Terminal Type And Quantity:** 3 tab, solder lug Shelf Life: N/a Unit Of Measure: **Demilitarization:**

No

# NSN 5905-00-892-0115

Precision Wire Wound Variable Resistor - Page 3 of 3

Fiig: A002a0

