NSN 5905-00-892-0379

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-892-0379 **Section Quantity: Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Overall Length:** 2.539 inches **Body Diameter:** 1.688 inches **Angle Of Mounting Hole In Deg:** 60.0 **Angle Between Centerlines Of Mounting Holes In Deg:** 120.0 **Shaft Diameter:** Between 0.373 inches and 0.376 inches **Shaft Length:** Between 0.969 inches and 1.031 inches **Body Length:** Between 1.428 inches and 1.508 inches **Overall Diameter:** 3.250 inches **Mounting Lip Diameter:** 3.00000 inches **Mounting Hole/stud Circle Diameter:** 0.875 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation: Mounting Facility Quantity: Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Unthreaded hole **Features Provided:**

Nonmetallic shaft

Electrical Resistance Per Section:

50.000 kilohms single section

NSN 5905-00-892-0379

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Rotary Actuator Travel In Angular Deg:
320.0
Power Dissipation Rating Per Section In Watts:
6.0 free air single section
Resistance Tolerance Per Section In Percent:
10.0/+10.0 single section
Actuator Travel Control Feature:
Spring
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
55.0 single section
Standard Taper Curve Per Section:
A single section
Special Features:
0.147 in. Mgt hole dia
Ferminal Type And Quantity:
3 threaded stud
Shelf Life:
N/a
Jnit Of Measure:
-
Demilitarization:
No
Filg:
A002a0