

View Online at <https://aerobasegroup.com/nsn/5905-00-892-1399>

Section Quantity:

1

Body Style:

Rectangular w/mounting holes/slots

Reliability Indicator:

Not established

Terminal Length:

0.594 inches

Mounting Hole Diameter:

0.093 inches

Shaft Diameter:

0.125 inches

Shaft Length:

0.062 inches

Body Length:

1.250 inches

Body Width:

0.250 inches

Body Height:

0.359 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

9000.0

Center To Center Distance Between Terminals:

0.700 inches

Lateral Distance Between Mounting Hole Centers:

1.000 inches

Mounting Facility Quantity:

2

Terminal Location:

Lower adjacent side two rows

Mounting Method:

Terminal and unthreaded hole

Center To Center Distance Between Terminal Rows:

0.100 inches

Features Provided:

Humidity proof

Electrical Resistance Per Section:

100.0 kilohms single section

Rotary Actuator Travel In Angular Deg:

9000.0

Center To Center Distance Between Center Terminal And Outside Terminal:

0.300 inches

Resistance Temperature Characteristic Range Per Section In Percent:

+0.0/+8.0 -55 degrees celsius single section and +0.0/+4.0 -25 degrees celsius single section and +0.0/+2.0 0 degrees celsius single section and -3.0/+3.0 85 degrees celsius single section and +0.0/+6.5 120 degrees celsius single section

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

Power Dissipation Rating Per Section In Watts:

0.25 free air single section

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Actuator Travel Control Feature:

Clutch

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0