NSN 5905-00-892-6542

Section Quantity:

Reliability Indicator:

Mounting Hole Diameter:

Not established **Body Diameter:**0.505 inches

0.118 inches

Body Style:Cylindrical

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-892-6542

Shaft Diameter:
0.343 inches
Shaft Length:
0.625 inches
Body Length:
1.531 inches
Shaft Style:
Round, slotted, undercut
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
3600.0
Maximum Starting Torque:
6.00 inch-ounces
Maximum Running Torque:
2.00 inch-ounces
Mounting Facility Quantity:
2
Terminal Location:
Rear end
Mounting Method:
Unthreaded hole
Features Provided:
Nonmetallic shaft
Electrical Resistance Per Section:
10.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
3600.0
Function Conformity Tolerance Per Section:
-0.25/+0.25 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
100.0 single section

NSN 5905-00-892-6542

Fiig: A002a0

Precision Wire Wound Variable Resistor - Page 2 of 2



Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -50.0/+100.0 single section **Power Dissipation Rating Per Section In Watts:** 1.0 free air single section **Function Conformity Per Section:** Single section independent linearity **Resistance Tolerance Per Section In Percent:** -2.0/+2.0 single section **Actuator Travel Control Feature:** Stops **Function Characteristic Per Section:** Single section linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section **Terminal Type And Quantity:** 3 turret Shelf Life: N/a **Unit Of Measure: Demilitarization:** No