## NSN 5905-00-892-6674

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-892-6674

Section Quantity:
1
Reliability Indicator:
Not established
First Flat Length:
0.219 inches
Flat Height:
0.216 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.500 inches
Shaft Style:
Round, flatted
Actuator Type:
Single shaft
Nonturn Device Radius:
0.531 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
100.000 kilohms single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Standard Taper Curve Per Section:
A single section
Special Features:
Bushing length 0.250
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 5905-00-892-6674

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Demilitarization:

No

Fiig:

A002a0