NSN 5905-00-892-6681

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-892-6681

Section Quantity:
1
Body Style:
Rectangular w/mounting holes
Reliability Indicator:
Not established
Mounting Hole Diameter:
0.093 inches
Mounting Slot Width:
0.078 inches
Shaft Diameter:
0.075 inches
Shaft Length:
0.035 inches
Body Length:
0.500 inches
Body Width:
0.220 inches
Body Height:
0.500 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
9000.0
Lateral Distance Between Mounting Hole Centers:
0.520 inches
Mounting Facility Quantity:
2
Terminal Location:
Rear end
Mounting Method:
Slot and terminal
Electrical Resistance Per Section:
5.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
9000.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
175.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-50.0/+50.0 single section

NSN 5905-00-892-6681

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No