NSN 5905-00-892-6785



View Online	at https://aerobasegroup.com/nsn/5905-00-892-6785
Section Qu	antity:
1	
Body Style	:
Cylindrical b	bushing mounted
Reliability I	ndicator:
Not establis	hed
Overall Ler	gth:
Between 1.2	281 inches and 1.375 inches
Body Diam	eter:
Between 0.8	390 inches and 0.922 inches
Shaft Diam	eter:
Between 0.2	248 inches and 0.251 inches
Shaft Leng	th:
Between 0.8	344 inches and 0.906 inches
Mounting E	Bushing Length:
Between 0.4	484 inches and 0.516 inches
Body Leng	th:
Between 0.4	437 inches and 0.469 inches
Overall Dia	meter:
1.274 inche	s
Shaft Style	•
Round, slot	ted
Actuator Ty	уре:
Single shaft	
Maximum S	Starting Torque:
6.00 inch-ou	inces
Maximum S	Stop Torque:

.

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

Between 0.422 inches and 0.454 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Locking bushing

NSN 5905-00-892-6785

Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:
1.5 kilohms single section
Rotary Actuator Travel In Angular Deg:
Between 251.0 and 318.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
120.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
10.0/+10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Test Data Document:
31349-mil-r-94 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
3 tab, solder lug
Specification Data:
31349-mil-r-94/5 government specification
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No