Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-892-9646

### Section Quantity:

1

Body Style:

Cylindrical bushing mounted

## **Reliability Indicator:**

Not established

#### **Body Diameter:**

2.031 inches

#### Shaft Diameter:

0.250 inches

#### Shaft Length:

0.750 inches

### Mounting Bushing Length:

0.375 inches

#### Body Length:

### 0.562 inches

Shaft Style:

#### Round

Actuator Type:

Single shaft

### Screw Thread Diameter:

0.250 inches

#### Screw Thread Series Designator:

Unef

# Screw Thready Qty Per Inch (tpi):

32.0

# **Terminal Location:**

Radially positioned over less than half the circumference

### Mounting Method:

Standard bushing

# **Features Provided:**

Humidity proof

# **Electrical Resistance Per Section:**

30.0 kilohms single section

# Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

# Power Dissipation Rating Per Section In Watts:

0.5 free air single section

# Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

# Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

55.0 single section

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Standard Taper Curve Per Section:

A single section

## Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

# Unit Of Measure:

---

# Demilitarization:

No

Fiig:

A002a0