NSN 5905-00-893-1312

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-893-1312 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established First Flat Length: 0.500 inches Flat Height: 0.187 inches **Body Diameter:** 0.937 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 1.125 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 0.719 inches **Shaft Style:** Round, flatted Switch Type: Rotary **Switch Voltage Rating In Volts:** 125.0 **Actuator Type:** Single shaft **Switch Operating Position:** Start of rotation **Switch Contact Arrangement:** Single pole, single throw, normally open, both positions maintained **Screw Thread Diameter:** 0.250 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Rear-bottom

Mounting Method: Standard bushing

NSN 5905-00-893-1312

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Features Provided:
Switch
Electrical Resistance Per Section:
10.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
320.0
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
20.0/+20.0 single section
Actuator Travel Control Feature:
Stops
Switch Current Type And Rating In Amps:
3.000 ac
Standard Taper Curve Per Section:
O single section
Terminal Type And Quantity:
5 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig:
A002a0