NSN 5905-00-893-2383
Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



Nonprecision Nonwire Woulld Valiable Resistor - Page 1 of 2			
View Online at https://aerobasegroup.com/nsn/5905-00-893-2383			
Section Quantity:			
1			
Body Style:			
Cylindrical bushing mounted			
Reliability Indicator:			
Not established			
liilength:			
1.125 inches			
Body Diameter:			
0.750 inches			
Shaft Diameter:			
0.125 inches			
Shaft Length:			
0.750 inches			
Mounting Bushing Length:			
0.250 inches			
Body Length:			
0.375 inches			
Shaft Style:			
Round			
Shaft Bearing Type:			
Bearing			
Actuator Type:			
Single shaft			
Nonturn Device Location:			
At 9 oclock			
Nonturn Device Radius:			
0.375 inches			
Screw Thread Diameter:			
0.250 inches			
Screw Thread Series Designator:			
Unef			
Screw Thready Qty Per Inch (tpi):			
32.0			
Mounting Method:			
Standard bushing			

**Electrical Resistance Per Section:** 

50.000 kilohms single section

**Power Dissipation Rating Per Section In Watts:** 

0.2 free air single section

**Function Conformity Per Section:** 

Single section independent linearity

## NSN 5905-00-893-2383

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Resistance	Tolerance	Per Section	In Percent

-20.0 to 20.0 single section

**Terminal Type And Quantity:** 

3 tab, solder lug

,

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A002a0