NSN 5905-00-893-5307

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-893-5307 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** Between 0.0570 inches and 0.0670 inches Pilot Length: Between 0.7490 inches and 0.7500 inches **Overall Length:** 1.526 inches **Undercut Diameter:** Between 0.749 inches and 0.750 inches **Undercut Width:** Between 0.0570 inches and 0.0670 inches **Body Diameter:** 0.969 inches **Shaft Diameter:** 0.1248 inches **Shaft Length:** 0.838 inches **Body Length:** 0.688 inches **Overall Diameter:** 1.250 inches **Mounting Lip Diameter:** 0.9690 inches **Mounting Lip Depth:** Between 0.0570 inches and 0.0670 inches **Shaft Style:** Round **Shaft Bearing Type:** Ball **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 354.0 **Maximum Starting Torque:**

0.50 inch-ounces **Maximum Running Torque:**

0.40 inch-ounces

NSN 5905-00-893-5307

Precision Wire Wound Variable Resistor - Page 2 of 3



Shaft End Play:
0.005 inches
Shaft Runout:
0.002 inches
Lateral Runout:
0.002 inches
Pilot Diameter Runout:
0.002 inches
Shaft Radial Play:
0.002 inches
End Application:
S-3b viking; h-60 seahwk aircraft
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring
Features Provided:
Humidity proof
Electrical Resistance Per Section:
20.0 kilohms single section
Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:
52.0 single section
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-1.00/+1.00 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
105.0 single section
Power Dissipation Rating Per Section In Watts:
1.25 free air single section
Function Conformity Per Section:
Single section independent linearity
Fixed Tap Quantity Per Section:
1 single section
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Continuous motion
Criticality Code Justification:
Feat
Tap Location From Ccw Terminal Per Section In Ohms:
10.0 single section
Function Characteristic Per Section:

Single section linear

NSN 5905-00-893-5307

A002a0

Precision Wire Wound Variable Resistor - Page 3 of 3



Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Special Features:
Weapon system essential
Precious Material And Location:
Terminals gold
Precious Material:
Gold
Terminal Type And Quantity:
4 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: