## NSN 5905-00-893-8664

Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-893-8664

Electrical Resistance:  130.000 ohms  Resistance Tolerance In Percent:  5.000/45.000  Ambient Tempurature In Deg Celsius At Full Rated Power:  25.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  25.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  350.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0/4350.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Not established  Body Diameter:  1.374 inches  Body Length:  1.875 inches  Power Dissipation Rating In Watts:  11.000 free air  Style Designator:  Avial terminal each end  Test Data Document:  131349-milize-4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  Via Unit Of Measure:  — Demilitarization:  No	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Resistance Tolerance In Percent: 5.0004-5.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0 Itempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/4-350.0 Inclosure Method: 6.6.capsulated Iteminal Type: Wire lead Reliability Indicator: Note established Red Appliance: 0.344 inches Red Appliance: 0.345 inches Power Dissipation Rating In Watts: 11.000 free air Style Designator: Avail terminal each end Test Dan Document: 81349-miliz-6-4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Via Unit Of Measure:	-260.0/+260.0
Resistance Tolerance In Percent: 5.000/+5.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 35.0.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 35.0.4-35.0.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Note stablished Body Diameter: 0.344 inches Body Length: 18.75 inches Power Dissipation Rating In Watts: 11.000 free air Style Designator: Axial terminal each end Test Data Document: sexcludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "', etc.) Shelf Life: Via Unit Of Measure:	Electrical Resistance:
Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 355.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/4350.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 1.344 inches Body Length: 1.875 inches Power Dissipation Rating In Watts: 11.000 free air Style Designator: Axial terminal each end Test Data Document: 28.1349-mitr26-4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Shelf Life: Via Unit Of Measure:	130.000 ohms
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/-350.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 3.344 inches Body Length: 11.757 inches Power Dissipation Rating In Watts: 111.000 free air Style Designator: Akkal terminal each end Test Data Document: 31349-milr26-4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Via Unit Of Measure:	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  350.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0/4350.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Not established  Body Diameter:  3.344 inches  Body Length:  1.875 inches  Power Dissipation Rating In Watts:  11.000 free air  Style Designator:  Availa terminal each end  Test Data Document:  31349-milr26-4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  W/a  Unit Of Measure:	-5.000/+5.000
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0+350.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.344 inches Body Length: 1.875 inches Power Dissipation Rating In Watts: 11.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr26-4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Shelf Life: Wa Unit Of Measure: — Demilitarization: No	Ambient Tempurature In Deg Celsius At Full Rated Power:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+350.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: -0.344 inches Body Length: -1.875 inches Power Dissipation Rating In Watts:	25.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:  155.0/+350.0  Inclosure Method: Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Not established  Body Diameter:  0.344 inches  Body Length:  1.875 inches  Power Dissipation Rating In Watts:  11.000 free air  Style Designator:  Avail terminal each end  Test Data Document:  31349-mili26-4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; accludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  Wa  Unit Of Measure:  Demilitarization:  No	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.344 inches Body Length: 1.875 inches Power Dissipation Rating In Watts: 11.000 free air Style Designator: Axial terminal each end Test Data Document: Bridden Style Designator: Axial terminal each end Test Data Document: Bridden Style Designator (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; Bridden Style Designator: Bridden Style Designator: Axial terminal each end Test Data Document: Bridden Style Designator (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; Bridden Style Designator: Bridden Style Designator: Axial terminal each end Test Data Document: Bridden Style Designator: Bridden Style De	350.0
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.344 inches Body Length: 1.875 inches Power Dissipation Rating In Watts: 11.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-miliz6-4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Not established  Body Diameter:  0.344 inches  Body Length:  1.875 inches  Power Dissipation Rating In Watts:  11.000 free air  Style Designator:  Axial terminal each end  Test Data Document:  81349-milr26-4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No	-55.0/+350.0
Terminal Type:  Wire lead  Reliability Indicator:  Not established  Body Diameter:  0.344 inches  Body Length:  1.875 inches  Power Dissipation Rating In Watts:  11.000 free air  Style Designator:  Axial terminal each end  Test Data Document:  81349-milr26-4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No	Inclosure Method:
Wire lead  Reliability Indicator:  Not established  Body Diameter: 0.344 inches  Body Length: 1.875 inches  Power Dissipation Rating In Watts: 11.000 free air  Style Designator:  Axial terminal each end  Test Data Document: 81349-milr26-4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No	Encapsulated
Reliability Indicator:  Not established  Body Diameter:  0.344 inches  Body Length:  1.875 inches  Power Dissipation Rating In Watts:  11.000 free air  Style Designator:  Axial terminal each end  Test Data Document:  81349-milr26-4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  Wa  Unit Of Measure:  Demilitarization:	Terminal Type:
Note stablished  Body Diameter:  0.344 inches  Body Length: 1.875 inches  Power Dissipation Rating In Watts: 11.000 free air  Style Designator:  Axial terminal each end  Test Data Document: 81349-milr26-4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  Wa  Unit Of Measure:  Demilitarization:  No	Wire lead
Body Length: 1.875 inches Power Dissipation Rating In Watts: 11.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr26-4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	Reliability Indicator:
D.344 inches  Body Length:  1.875 inches  Power Dissipation Rating In Watts:  11.000 free air  Style Designator:  Axial terminal each end  Test Data Document:  B1349-milr26-4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:	Not established
Body Length:  1.875 inches  Power Dissipation Rating In Watts:  11.000 free air  Style Designator:  Axial terminal each end  Test Data Document:  B1349-milr26-4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:	Body Diameter:
1.875 inches  Power Dissipation Rating In Watts: 11.000 free air  Style Designator:  Axial terminal each end  Test Data Document:  81349-milr26-4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formate excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:	0.344 inches
Power Dissipation Rating In Watts:  11.000 free air  Style Designator:  Axial terminal each end  Test Data Document:  31349-milr26-4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  W/a  Unit Of Measure:  Demilitarization:	Body Length:
11.000 free air  Style Designator:  Axial terminal each end  Test Data Document:  B1349-milr26-4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:	1.875 inches
Style Designator:  Axial terminal each end  Test Data Document:  81349-milr26-4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formative excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:	Power Dissipation Rating In Watts:
Axial terminal each end  Test Data Document:  B1349-milr26-4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formative excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:	11.000 free air
Test Data Document:  81349-milr26-4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No	Style Designator:
B1349-milr26-4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formative excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No	Axial terminal each end
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No	Test Data Document:
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No	81349-milr26-4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format
Shelf Life: N/a Unit Of Measure: Demilitarization: No	excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
N/a Unit Of Measure:  Demilitarization:	and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Unit Of Measure: Demilitarization:	Shelf Life:
 Demilitarization: No	N/a
No	Unit Of Measure:
No	<del></del>
	Demilitarization:
Filg:	No
	Fiig:
A001a0	A001a0