

View Online at <https://aerobasegroup.com/nsn/5905-00-895-3631>

**Section Quantity:**

3

**Body Style:**

Cylindrical bushing mounted

**Reliability Indicator:**

Not established

**Body Diameter:**

1.750 inches

**Shaft Diameter:**

0.250 inches

**Shaft Length:**

1.375 inches

**Mounting Bushing Length:**

0.375 inches

**Body Length:**

3.125 inches

**Shaft Style:**

Round

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

9000.0

**Nonturn Device Location:**

At 9 oclock

**Nonturn Device Radius:**

0.531 inches

**Screw Thread Diameter:**

0.375 inches

**Screw Thread Series Designator:**

Unef

**Screw Thready Qty Per Inch (tpi):**

32.0

**Terminal Location:**

Rear end

**Mounting Method:**

Standard bushing

**Features Provided:**

Humidity proof

**Electrical Resistance Per Section:**

2.5 kilohms all sections

**Rotary Actuator Travel In Angular Deg:**

9000.0

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

140.0 all sections

**Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:**

-30.0/+30.0 all sections

**Power Dissipation Rating Per Section In Watts:**

3.0 free air all sections

**Resistance Tolerance Per Section In Percent:**

-5.0/+5.0 all sections

**Actuator Travel Control Feature:**

Clutch

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

65.0 all sections

**Standard Taper Curve Per Section:**

A all sections

**Terminal Type And Quantity:**

3 binding post

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0