

View Online at https://aerobasegroup.com/nsn/5905-00-895-7626

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

## **Reliability Indicator:**

Not established

#### **Overall Length:**

1.219 inches

#### **Body Diameter:**

2.000 inches

#### Shaft Diameter:

0.250 inches

### Shaft Length:

0.219 inches

### Mounting Bushing Length:

# 0.500 inches

**Body Length:** 

1.000 inches

### **Overall Diameter:**

2.250 inches

## Shaft Style:

Round

### Actuator Type:

Single shaft

# Effective Electrical Rotation In Deg Angular Rotation:

350.0

### Maximum Starting Torque:

0.60 inch-ounces

### **Terminal Location:**

Radially positioned over less than half the circumference

### Mounting Method:

Clamp ring

#### **Electrical Resistance Per Section:**

100.0 kilohms single section

### Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:

330.0 3rd section

# **Rotary Actuator Travel In Angular Deg:**

354.0

### **Function Conformity Tolerance Per Section:**

-0.50/+0.50 single section

## Power Dissipation Rating Per Section In Watts:

4.0 free air single section



**Function Conformity Per Section:** Single section independent linearity Fixed Tap Quantity Per Section: 3 single section **Resistance Tolerance Per Section In Percent:** -5.0/+5.0 single section **Actuator Travel Control Feature:** Stops **Function Characteristic Per Section:** Single section linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 25.0 single section **Terminal Type And Quantity:** 6 solder stud Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A002a0