NSN 5905-00-895-7629

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-895-7629 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 1.9370 inches Pilot Length: 0.0310 inches **Undercut Diameter:** 1.9375 inches **Undercut Width:** 0.0310 inches **Body Diameter:** 2.000 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.938 inches **Body Length:** 0.968 inches **Mounting Lip Diameter:** 2.0000 inches **Mounting Lip Depth:** 0.0310 inches **Shaft Style:** Round **Shaft Bearing Type:** Ball **Contact Arm Electrical Off Position:** Fully ccw **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 350.0 **Maximum Starting Torque:** 0.60 inch-ounces **Maximum Running Torque:**

0.60 inch-ounces

Shaft End Play:

0.006 inches

NSN 5905-00-895-7629

Fiig: A002a0

Precision Wire Wound Variable Resistor - Page 2 of 2



Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
100.0 percent, rated amperes c and better flooring
Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:
20.0 single section and 100.0 single section and 175.0 single section and 250.0 single section and 330.0 single section
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-0.50/+0.50 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
80.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-150.0/+150.0 single section
Power Dissipation Rating Per Section In Watts:
4.0 7th secondary quality
Function Conformity Per Section:
Single section terminal base linearity
Fixed Tap Quantity Per Section:
5 single section
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
7 oclock all primaries
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
25.0 single section
Special Features:
Drive coupling on shaft
Terminal Type And Quantity:
12 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No