NSN 5905-00-895-7648

Section Quantity:

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-895-7648

Body Style:
Cylindrical friction mounted
Reliability Indicator:
Not established
Overall Length:
1.218 inches
Body Diameter:
2.000 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.250 inches
Body Length:
0.968 inches
Overall Diameter:
2.375 inches
Shaft Style:
Round
Shaft Bearing Type:
Ball
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
350.0
Maximum Starting Torque:
0.60 inch-ounces
Maximum Running Torque:
0.60 inch-ounces
Shaft End Play:
0.006 inches
Fragility Factor:
Moderately delicate
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring
Cubic Measure:
5.396 cubic inches
Electrical Resistance Per Section:
100.0 kilohms single section

NSN 5905-00-895-7648

Precision Wire Wound Variable Resistor - Page 2 of 2



Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:

175.0 single section and 198.0 single section and 264.0 single section and 290.7 single section

Rotary Actuator Travel In Angular Deg:

360.0

Function Conformity Tolerance Per Section:

-0.50/+0.50 single section

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

80.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-150.0/+150.0 single section

Power Dissipation Rating Per Section In Watts:

4.0 free air single section

Function Conformity Per Section:

Single section independent linearity

Fixed Tap Quantity Per Section:

4 single section

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 single section

Actuator Travel Control Feature:

Continuous motion

Function Characteristic Per Section:

Single section linear

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

25.0 single section

Terminal Type And Quantity:

7 turret

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0