Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-896-9409

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Overall Length:

1.700 inches

Body Diameter:

1.160 inches

Shaft Diameter:

0.250 inches

Shaft Length:

0.710 inches

Mounting Bushing Length:

0.375 inches

Body Length:

0.750 inches

Overall Diameter:

1.460 inches

Shaft Style:

Round

Actuator Type:

Double ended shaft

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

Between 0.526 inches and 0.536 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

10.0 kilohms single section

Power Dissipation Rating Per Section In Watts:

2.0 free air single section



Resistance Tolerance Per Section In Percent: -10.0/+10.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section Standard Taper Curve Per Section: A single section Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A002a0