

View Online at <https://aerobasegroup.com/nsn/5905-00-897-0024>

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Overall Length:

Between 1.374 inches and 1.716 inches

Body Diameter:

Between 1.500 inches and 1.710 inches

Shaft Diameter:

Between 0.248 inches and 0.251 inches

Shaft Length:

Between 0.844 inches and 0.906 inches

Mounting Bushing Length:

Between 0.360 inches and 0.390 inches

Body Length:

Between 0.530 inches and 0.810 inches

Overall Diameter:

2.135 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

Between 280.0 and 305.0

Maximum Starting Torque:

6.00 inch-ounces

Maximum Stop Torque:

128.00 inch-ounces

Nonturn Device Location:

At 9 oclock

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing and shaft w/panel seal

Electrical Resistance Per Section:

250.0 ohms single section

Rotary Actuator Travel In Angular Deg:

Between 280.0 and 305.0

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

105.0 single section

Power Dissipation Rating Per Section In Watts:

4.0 free air single section

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0