Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-897-0656

Section Quantity: 1 **Body Style:** Rectangular w/mounting holes/slots **Reliability Indicator:** Not established **Overall Length:** Between 1.310 inches and 1.330 inches **Terminal Length:** 11.500 inches **Overall Height:** Between 0.310 inches and 0.330 inches **Overall Width:** Between 0.180 inches and 0.200 inches **Mounting Hole Diameter:** 0.088 inches Shaft Diameter: Between 0.105 inches and 0.115 inches Shaft Length: 0.250 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** Between 1.240 inches and 1.260 inches **Body Width:** Between 0.180 inches and 0.200 inches **Body Height:** Between 0.310 inches and 0.330 inches Shaft Style: Round, slotted Actuator Type: Single shaft Maximum Starting Torque: 5.00 inch-ounces Lateral Distance Between Mounting Hole Centers: Between 0.995 inches and 1.005 inches Screw Thread Diameter: 0.190 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi):

32.0



Terminal Location:
Rear end
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
200.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
7920.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-500.0/+300.0 single section
Power Dissipation Rating Per Section In Watts:
0.25 heat sink single section
Resistance Tolerance Per Section In Percent:
-20.0/+20.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
50.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0