Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-897-1281

### Section Quantity:

1

Body Style:

Cylindrical tab/flange mounted

### **Reliability Indicator:**

Not established

#### **Overall Length:**

0.312 inches

#### **Body Diameter:**

0.688 inches

#### Mounting Hole Diameter:

0.090 inches

#### Body Length:

0.312 inches

#### **Overall Diameter:**

1.250 inches

# Actuator Type:

Flush drive with slot-hole

## Effective Electrical Rotation In Deg Angular Rotation:

360.0

### Lateral Distance Between Mounting Hole Centers:

1.000 inches

### Mounting Facility Quantity:

2

# **Terminal Location:**

Radially positioned over less than half the circumference

# Mounting Method:

Unthreaded hole

# **Electrical Resistance Per Section:**

39.5 ohms single section

# Rotary Actuator Travel In Angular Deg:

360.0

# **Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 single section

# Actuator Travel Control Feature:

Continuous motion

# Standard Taper Curve Per Section:

A single section

# Terminal Type And Quantity:

3 tab, solder lug

# Shelf Life:

N/a

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0