

View Online at <https://aerobasegroup.com/nsn/5905-00-897-5370>

Section Quantity:

1

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

Between 1.8745 inches and 1.8750 inches

Pilot Length:

0.0600 inches

Overall Length:

3.295 inches

Undercut Diameter:

1.875 inches

Undercut Width:

0.0600 inches

Body Diameter:

2.000 inches

Shaft Diameter:

0.250 inches

Shaft Length:

2.250 inches

Body Length:

0.985 inches

Overall Diameter:

2.000 inches

Mounting Lip Diameter:

2.0000 inches

Mounting Lip Depth:

0.0600 inches

Shaft Style:

Round

Shaft Bearing Type:

Bearing

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

350.0

Maximum Starting Torque:

0.30 inch-ounces

Terminal Location:

Radially positioned over more than half the circumference

Mounting Method:

Clamp ring

Electrical Resistance Per Section:

10.0 kilohms single section

Rotary Actuator Travel In Angular Deg:

360.0

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

Power Dissipation Rating Per Section In Watts:

4.0 free air single section

Fixed Tap Quantity Per Section:

1 single section

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Actuator Travel Control Feature:

Continuous motion

Tap Location From Ccw Terminal Per Section In Ohms:

5000.0 single section

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

4 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0