

View Online at <https://aerobasegroup.com/nsn/5905-00-897-5621>

Section Quantity:

1

Body Style:

Cylindrical friction mounted

Reliability Indicator:

Not established

Overall Length:

1.218 inches

Body Diameter:

2.000 inches

Shaft Diameter:

0.250 inches

Shaft Length:

0.250 inches

Body Length:

0.968 inches

Overall Diameter:

2.375 inches

Shaft Style:

Round

Shaft Bearing Type:

Ball

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

350.0

Maximum Starting Torque:

0.60 inch-ounces

Maximum Running Torque:

0.60 inch-ounces

Shaft End Play:

0.006 inches

Fragility Factor:

Moderately delicate

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Clamp ring

Cubic Measure:

5.396 cubic inches

Electrical Resistance Per Section:

10.0 kilohms single section

Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:

175.0 single section and 210.0 single section

Rotary Actuator Travel In Angular Deg:

360.0

Function Conformity Tolerance Per Section:

-0.50/+0.50 single section

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

80.0 single section

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-150.0/+150.0 single section

Power Dissipation Rating Per Section In Watts:

4.0 free air single section

Function Conformity Per Section:

Single section independent linearity

Fixed Tap Quantity Per Section:

2 single section

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 single section

Actuator Travel Control Feature:

Continuous motion

Function Characteristic Per Section:

Single section linear

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

25.0 single section

Terminal Type And Quantity:

5 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0